



- La macchina permette il montaggio dei fianchi, la ripassatura di tutto il bordo montato della scarpa e la contemporanea rifilatura della parte eccedente di tomaia e intersuola.
 - La velocità e la larghezza del bordo rifilato sono regolabili istantaneamente.
 - La forza di pinzatura dei dischi operatori e lo spazio tra di essi sono velocemente variabili
 - Il disco superiore è riscaldato per ottenere la riattivazione del collante ottimizzando il risultato di montaggio.
 - Il particolare sistema di taglio permette di operare perfettamente con intersuola in cuoio e/o gomma fino a spessore di 10-12 mm.
 - Machine allows side-lasting, all lasted edge repassing and in the same, trimming of the exceeding part of the upper and insole.
 - Speed of disks and the largest of edge to trim are instantaneously regulable.
 - Pressing pincer-effect and space between operating disks are quickly variable.
 - The highest disk is provided with heating system to improve cement reactivation and lasting result.
 - A particular cutting system allows to operate a perfectly with insole in cuir or/and rubber up to thickness of 10-12 millimeters.

DATI TECNICI | TECHNICAL DATA

Dimensioni | Dimensions: cm. 80x67x120 h

Peso netto | Net weight: Kg. 170

Consumo elettrico | Electric consumption: Kw 3.0



0331 551025



sales@bombelli-spa.com



bombelli-spa.com



bombelli S.p.A.